

Accessory List

SFP Module #	Description
SFP100-MM-550	SFP 100Mbps Multimode LC Transceiver 550m, 850nm, -40°C to +85°C
SFP100-MM-2	SFP 100Mbps Multimode LC Transceiver 2km, 1310nm, -40°C to +85°C
SFP100-SM-20	SFP 100Mbps Singlemode LC Transceiver 20km, 1310nm, -40°C to +85°C
SFP100-SM-40	SFP 100Mbps Singlemode LC Transceiver 40km, 1300nm, -40°C to +85°C
SFP100-SM-60	SFP 100Mbps Singlemode LC Transceiver 60km, 1310nm, -40°C to +85°C
SFP100-SM-100	SFP 100Mbps Singlemode LC Transceiver 100km, 1550nm, -40°C to +85°C
SFP100-SM-120	SFP 100Mbps Singlemode LC Transceiver 120km, 1550nm, -40°C to +85°C
SFP100BIDI1-SM-20	SFP 100Mbps Bi-Directional Singlemode LC Transceiver 20km, TX1310nm, RX1550nm, -40°C to +85°C
SFP100BIDI2-SM-20	SFP 100Mbps Bi-Directional Singlemode LC Transceiver 20km, TX1550nm, RX1310nm, -40°C to +85°C
SFP100BIDI1-SM-40	SFP 100Mbps Bi-Directional Singlemode LC Transceiver 40km, TX1310nm, RX1550nm, -40°C to +85°C
SFP100BIDI2-SM-40	SFP 100Mbps Bi-Directional Singlemode LC Transceiver 40km, TX1550nm, RX1310nm, -40°C to +85°C
SFP100BIDI1-SM-60	SFP 100Mbps Bi-Directional Singlemode LC Transceiver 60km, TX1310nm, RX1550nm, -40°C to +85°C
SFP100BIDI2-SM-60	SFP 100Mbps Bi-Directional Singlemode LC Transceiver 60km, TX1550nm, RX1310nm, -40°C to +85°C
SFP100-TX	SFP 100Mbps TX RJ45 Transceiver 100m, -40°C to +85°C
SFP1000-TX	SFP 1000Mbps TX RJ45 Transceiver 100m, -40°C to +85°C
SFP1000-MM-550	SFP 1Gbps Multimode LC Transceiver 550m, 850nm, -40°C to +85°C
SFP1000-MM-2	SFP 1Gbps Multimode LC Transceiver 2km, 1310nm, -40°C to +85°C
SFP1000-SM-10	SFP 1Gbps Singlemode LC Transceiver 10km, 1310nm, -40°C to +85°C
SFP1000-SM-20	SFP 1Gbps Singlemode LC Transceiver 20km, 1310nm, -40°C to +85°C
SFP1000-SM-40	SFP 1Gbps Singlemode LC Transceiver 40km, 1310nm, -40°C to +85°C
SFP1000-SM-60	SFP 1Gbps Singlemode LC Transceiver 60km, 1550nm, -40°C to +85°C
SFP1000-SM-80	SFP 1Gbps Singlemode LC Transceiver 80km, 1550nm, -40°C to +85°C
SFP1000BIDI1-SM-10	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 10km, TX1310nm, RX1550nm, -40°C to +85°C
SFP1000BIDI2-SM-10	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 10km, TX1550nm, RX1310nm, -40°C to +85°C
SFP1000BIDI1-SM-20	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 20km, TX1310nm, RX1550nm, -40°C to +85°C
SFP1000BIDI2-SM-20	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 20km, TX1550nm, RX1310nm, -40°C to +85°C
SFP1000BIDI1-SM-40	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 40km, TX1310nm, RX1550nm, -40°C to +85°C
SFP1000BIDI2-SM-40	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 40km, TX1550nm, RX1310nm, -40°C to +85°C
SFP1000BIDI1-SM-60	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 60km, TX1310nm, RX1550nm, -40°C to +85°C
SFP1000BIDI2-SM-60	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 60km, TX1550nm, RX1310nm, -40°C to +85°C
SFP1000BIDI1-SM-80	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 80km, TX1310nm, RX1550nm, -40°C to +85°C
SFP1000BIDI2-SM-80	SFP 1Gbps Bi-Directional Singlemode LC Transceiver 80km, TX1550nm, RX1310nm, -40°C to +85°C
SFP10G-TX	SFP 10Gbps TX RJ45 Copper
SFP10G-MM-300	SFP 10Gbps Multimode LC Transceiver 300m, 850nm, -40°C to +85°C
SFP10G-SM-10	SFP 10Gbps Singlemode LC Transceiver 10km, 1310nm, -40°C to +85°C
SFP10G-SM-40	SFP 10Gbps Singlemode LC Transceiver 40km, 1310nm, -40°C to +85°C
SFP10G-SM-80	SFP 10Gbps Singlemode LC Transceiver 80km, 1310nm, 0°C to +70°C

SFP Module #	Description	Exceptions
SFP-SGMII-TX	SFP 10/100/1000Mbps TX RJ45, SGMII Transceiver 100m, -40°C to +85°C	Used on iRBX6GF Ports 1-2 & 3-4 Only
SFP100-SGMII-MM	SFP 100Mbps SGMII, Multimode LC Transceiver 2km, 1310nm, -40°C to +85°C	Used on iRBX6GF Ports 1-2 & 3-4 Only
SFP100-MM-2-SG	SFP 100Mbps Multimode LC Transceiver 2km, 850nm, -40°C to +85°C	Used on iSG18GFP Only
SFP100-SM-10-SG	SFP 100Mbps Singlemode LC Transceiver 10km, 1310nm, -40°C to +85°C	Used on iSG18GFP Only
SFP100-SM-40-SG	SFP 100Mbps Singlemode LC Transceiver 40km, 1310nm, -40°C to +85°C	Used on iSG18GFP Only
SFP100-SM-80-SG	SFP 100Mbps Singlemode LC Transceiver 80km, 1550nm, -40°C to +85°C	Used on iSG18GFP Only
SFP1000-MM-2-SG	SFP 1Gbps Multimode LC Transceiver 2km, 1310nm, -40°C to +85°C	Used on iSG18GFP Only
SFP1000-SM-10-SG	SFP 1Gbps Singlemode LC Transceiver 10km, 1310nm, -40°C to +85°C	Used on iSG18GFP Only
SFP1000-SM-40-SG	SFP 1Gbps Singlemode LC Transceiver 40km, 1310nm, -40°C to +85°C	Used on iSG18GFP Only
SFP1000-SM-80-SG	SFP 1Gbps Singlemode LC Transceiver 80km, 1550nm, -40°C to +85°C	Used on iSG18GFP Only
SFP-SGMI-TX-SG	SFP 10/100/1000Mbps TX RJ45, SGMII Transceiver 100m, -40°C to +85°C	Used on iSG18GFP Only

Additional Accessories	Description
Conformal Coating	
C1	DIN Rail Products & Rack Products
Antennas	
1900-0002	Antenna with 2m cable
1900-0003	Antenna with 5m cable
1900-0019	Antenna with 15m cable
Cables	
1900-0004	Type B plug A/C power cord
1900-0014	Ethernet Cable CAT5E 3ft
Mounting Kits	
1900-0007	19" Rack mount tray for DIN products Applies to: iES6-S, iES8-S, iES10G-S
1900-0009	DIN Rail Bracket Kit for DIN products V1 Applies to: iES6-S, iES8-S, iES8G, iES10G-S, iES10GF, iES12G, iES12GP, iES20GF, iES22GF, iDS6, iDS6P-S, iMC2G, iRBX6GF
1900-0008	DIN Rail Bracket Kit for DIN products V2 Applies to: iMC2G, iMC4F, iSC2F, iSG18GFP, uES4F
1900-0005	DIN Rail Clip Kit for DIN products Applies to: uES4F-S, iPJ2G, iDS3-S
1900-0006	Panel Mount Kit for DIN Products Applies to: iES6-S, iES8-S, iES8G, iES10G-S, iES10GF, iES12G, iES12GP, iES20GF, iES22GF, iDS6, iDS6P-S, iMC2G, iMC4F, iRBX6GF, iRBX6GF-S, iSC2F, iSG18GFP, uES4F
1900-0011	Rack Mount Kit for 19" Rack products V1 (2 brackets) Applies to: iES26GF
1900-0012	Rack Mount Kit for 19" Rack products V2 (4 brackets) Applies to: iES28GF, iES28TG, iDS24GF, iMX350, iMX950
Power Supplies	
1900-0010	External 250W Power Supply: Input 90-350VDC or 100-240VAC Applies to: iTS12GP, iES12GP (E)
Upgrades	
1931-0001	Upgrade - iMX350 to iMX950